

NCDEQ Division of Energy, Mineral and Land Resources

**Stormwater Discharge Monitoring Report (DMR) Form for NCG190000
Marinas and Shipbuilding**

[Click here for instructions](#)

Complete, sign, scan and submit the DMR via the [Stormwater NPDES Permit Data Monitoring Report \(DMR\) Upload form](#) within 30 days of receiving sampling results. Mail the original, signed hard copy of the DMR to the [appropriate DEMLR Regional Office](#).

Certificate of Coverage No. NCG19	Person Collecting Samples:
Facility Name:	Laboratory Name:
Facility County:	Laboratory Cert. No.:
Discharge during this period: <input type="checkbox"/> Yes <input type="checkbox"/> No (if no, skip to signature and date)	
Has your facility implemented mandatory Tier response actions <u>this sample period</u> for any benchmark exceedances? <input type="checkbox"/> Yes <input type="checkbox"/> No If so, which Tier (I, II, or III)?	
A copy of this DMR has been uploaded electronically via https://edocs.deq.nc.gov/Forms/SW-DMR <input type="checkbox"/> Yes <input type="checkbox"/> No	
Date Uploaded:	

Analytical Monitoring Requirements for Outfalls with Industrial Activities – Benchmarks in (Red)

Parameter Code	Parameter	Outfall	Outfall	Outfall	Outfall	Outfall
N/A	Receiving Stream Class					
N/A	Date Sample Collected MM/DD/YYYY					
46529	24-Hour Rainfall in inches					
CO530	TSS in mg/L (100 or 50*)					
00552	Non-Polar Oil & Grease in mg/L (15)					
00340	Chemical Oxygen Demand in mg/L (120)					
00400	pH in standard units (6.0 – 9.0)					
01105	Aluminum, total recoverable in mg/ L (0.75 FW, 0.24 SW)					
01027	Chromium III, total recoverable in mg/L at certain facilities** (0.905 FW, none SW)					
CO034	Chromium VI, total recoverable in mg/L at certain facilities** (0.016 FW, 1.1 SW)					
01042	Copper, total recoverable in mg/L (0.010 FW, 0.006 SW)					
01051	Lead, total recoverable (as Pb) in mg/ L (0.075 FW, 0.22 SW)					
CO034	Nickel, total recoverable in mg/L (0.335 FW, 0.074 SW)					
01092	Zinc, total recoverable in mg/L (0.126 FW, 0.095 SW)					
NCOIL	Estimated New Motor/Hydraulic Oil Usage in gal/month					

*Outfalls to Outstanding Resource Waters (ORW), High Quality Waters (HQW), Trout Waters (Tr) and Primary Nursery Areas (PNA) have a benchmark TSS limit of 50 mg/L. All other water classifications have a benchmark of 100 mg/L

**Only required for Ship and Boat Building and Repairing [SIC 373] facilities that perform metal fabrication in areas that could potentially be exposed to stormwater

FW (Freshwater) **SW** (Saltwater)

Notes (optional):

"I certify by my signature below, under penalty of law, that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fines and imprisonment for knowing violations."

Signature of Permittee or Delegated Authorized Individual

Date

Email Address

Phone Number