UST-8

NOTIFICATION FOR ACTIVITIES INVOLVING UNDERGROUND STORAGE TANK SYSTEMS (USTs)



RETURN COMPLETED FORM NC DEQ / DWM / UST SECTION 1646 MAIL SERVICE CENTER RALEIGH, NC 27699-1646

ATTN: REGISTRATION & PERMITTING PHONE (919) 707-8171 FAX (919) 715-1117

UST.Permits@deq.nc.gov http://www.wastenotnc.org/

STATE USE ONLY								
I.D. #_								
0								
Count	у							

Underground Storage Tank (UST) system owners and operators are required by federal and state law to provide notification for all UST systems that were in the ground on or after May 8, 1986, unless taken out of operation on or before January 1, 1974. In addition, registration of commercial USTs in use on or after January 1, 1989 is necessary to comply with state law (N.C.G.S. 143-215.94C).

A UST system <u>owner</u> is: (a) in the case of a UST system in use on November 8, 1984, or brought into use after that date, any person who owns a UST system used for storage, use, or dispensing of regulated substances; and (b) in the case of any UST system in use before November 8, 1984, but no longer in use on that date, any person who owned such UST immediately before the discontinuation of its use.

A UST system <u>operator</u> is any person in control of, or having responsibility for, the daily operation of a UST system.

The primary purpose of this notification form is to obtain and update information on UST system locations, ownership, construction, product stored, leak detection and corrosion protection methods, etc. and to facilitate permitting and the payment of annual operating fees. It is expected that the information provided will be based on reasonably available records, or, in the absence of such records, personal knowledge, belief, or recollection.

Which USTs are included?

Regulated and/or commercial USTs, including the following:

- USTs used to store or resell petroleum product (e.g., motor fuels, jet fuels, waste oil, kerosene, varsol, transmission fluid, mineral spirits, gasohol, etc.)
- Heating oil USTs > 1,100 gallons (gals)
- Farm or residential USTs > 1,100 gals
- Emergency generator USTs
- Hydraulic lift USTs
- Oil-water separator USTs (containing petroleum in amounts > 1% of tank capacity)
- Hazardous substance USTs > 110 gals (e.g., alcohols, naphthalene, dry cleaning fluids, antifreeze, formaldehyde, hexane, etc.)
- Airport Hydrant Fuel Distribution Systems
- USTs with Field Constructed Tanks

Which USTs are excluded?

Certain tanks are not included in these notification requirements. These tanks include the following: small home heating oil and farm tanks (\leq 1,100 gals), large heating oil tanks (> 1,100 gals) if used to heat four or fewer households and located on premises where used, septic tanks, storm water or waste water collection systems, flow-through process tanks, and tanks situated in an underground area (such as a basement, cellar, mine, shaft, vault or tunnel) if the tank is situated upon or above the surface of the floor.

INSTRUCTIONS

Please type or print all items except signature. This form must be completed by an owner or operator for each facility containing UST systems. If more than four (4) UST systems are owned at a facility, photocopy the necessary additional sheets and staple to this form.

Complete sections I through VI.A. and IX completely. Then only complete the applicable sections of VI.B. through VIII.										
I. OWNERSHIP OF UST SYSTEM			II. OPERATOR OF UST SYSTEM Check if same as owner							
Owner Name (Corporation, Individual, Public Agency, or Other Entity)			Operator Name (Corporation, Individual, Public Agency, or Other Entity)							
Contact Name (if not named above)			Contact Name (if not named above)							
Street Address			Street Address							
City	St	State	Zip Code	City		State	Zip Code			
County				County						
Phone Number	e Number Fax Number			Phone Number	Fa	Fax Number				
Email Address			Email Address							
☐ Check here if "Real" Property Owner of Site			Check here if "Real" Property Owner of Site							
Type of UST owner (check all that apply):										
State Gov't Local	vate/Corporate									
☐ Federal Gov't GSA Facility ID										
III. TYPE OF NOTIFICATION	ipply)									
Amendment of a previous registration in the sections that follow that has UST-8 submittal) Temporary closure (Complete see Existing Facility with UST system (see fee payment instructions at	evious UST-6 or	Change of Ownership A "Change of Owners documents showing t property deed, etc.) r Failure to complete a ownership status	ship" form, UST the transfer of ta <u>nust</u> accompan	ank ownership y this form.	(e.g., bill of sale,					

UST-8 NOTIFICATION FOR AC	TIVIT	IES INVOLVING U	INDERGROUND STO	RAGE TANK SYST	EMS (USTs) DEO			
IV. LOCATION OF UST SYSTEM								
Facility Name or Company			Indicate number of regula	ated tanks at this location				
Street Address			Indicate number of regulated tanks at this location					
City Zip Code			Indicate total number of tanks at this location					
			Check box if tanks are lo	cated on land within an In	dian reservation			
County	Phor	ne Number	S. S. S. S. S. Marian Mana					
County Tax Map Number:			Are any UST systems at this facility located Yes No within 500 feet of a water supply well?					
Facility ID (if known):								
V. CONTACT PERSON FOR UST LO	CAT	ION						
Name		Job Title		Phone Number				
VI. DESCRIPTION OF ALL UST OR	СОМІ	LARTMENT SYST	EMS AT THIS FACIL	ITY				
A. UST Information								
Tank/Compartment ID# (e.g., A, B, C or 1, 2, 3; If compartment tank 1A, 1B, 1C, etc.)	Tank	No.	Tank No.	Tank No.	Tank No.			
Date of Installation								
Tank Manufacturer								
Tank Model								
Materials of construction ¹								
If Other (specify)								
Field Constructed Tank								
Capacity (gallons) If compartment tank, list compartment size.								
Check if tank is siphon manifolded and enter tank # it is manifolded with.	<u> </u>				□ /			
Product stored ²	<u> </u>							
If Hazardous substance, Chemical Abstract Service (CAS) number								
Other (specify)								
Enter one of the following in the space provided: E (e.g. ACT-100-U), DW* Steel/Jacketed (e.g., Perm SW** Steel/Polyurethane (e.g., ACT-100-U) *DW = Double-walled **SW = Single-walled ***I Enter one of the following in the space provided: A Heating Oil, Kerosene, Motor Oil, Other Non-Petro	natank, ⁻ FRP = F viation	Titan), Other, SW** FRP** Fiberglass Reinforced Plas Gas, Biodiesel (> 20%) - D	* (e.g., Xerxes, Containment So tic Diesel Mix, Diesel, Ethanol (> 10	lutions), SW** Steel, SW** St	eel/FRP*** (e.g., ACT-100),			
B. Piping System			1					
	Tank	(No.	Tank No.	Tank No.	Tank No.			
Piping Manufacturer	1							
Piping Model	1							
Material of Construction ¹	1							
If Other (specify)	1							
Airport Hydrant System	1							
Piping configuration (Pressurized, Suction, European Suction, Gravity)								
If suction, check valve located at? (Tank, Dispenser, or Both)								
 Enter one of the following in the space provided: Definition of the following in the space provided: Metal/Plastic (e.g., PetrofuseZP), DW* PVC, DW* *DW = Double-walled **SW = Single-walled ***Inches ***Inches	Steel, N	lone, Other, SW** Copper	, SW** Flex, SW** FRP, SW** F		ed Thread IIA), DW*			

UST-8 2 Revised 3/20/2018

								•
C. Under Dispenser Containment (U	DC)							
Enter the dispenser number(s) in each column the "ALL" as the number in column 1 and complete of dispensers that have that model UDC.								
	Dispenser #	(s)	Dispenser #	#(s)	Dispenser #	(s)	Dispenser #(s)
UDC Manufacturer								
UDC Model								
Is UDC Single (SW) or Double Walled (DW)? 1								
Method of monitoring UDC ²								
UDC Material of Construction ³								
If Other (specify)								
¹ Enter one of the following choices: SW (single-	walled) or DW	/ (double-wall	ed)					
² Enter one of the following choices: Sump Sens		•		one				
³ Enter one of the following choices: Plastic, FRF								
D. Leak detection (LD) ¹ [Check any box		on of boxes th		er to 15A NCA		0505, .0900 a		
Mark all that apply	Tank No.		Tank No.	I	Tank No.		Tank No.	
	Tank	Piping	Tank	Piping	Tank	Piping	Tank	Piping
a. Automatic tank gauging								
b. Manual tank gauging ²								
c. Interstitial monitoring								
i. Method of Monitoring Interstice ¹								
d. Statistical inventory reconciliation								
e. Groundwater monitoring every 14 days ³								
f. Vapor monitoring every 14 days								
g. Automatic line leak detector ⁴								
i. Mechanical line leak detector								
ii. Electronic line leak detector								
h. Periodic line tightness testing								
 i. Exempt under 40 CFR 280.41 (b) (2) (i)- (iv) (this exemption applies only to "European" suction systems) 								
j. Automatic tank gauging and Tank Tightness Testing ⁵								
k. Vapor Monitoring with Tracer compound ⁵								
I. Inventory Control per DoD 4140.25 and one of the following: ⁵								
i. Tank Tightness Test ⁵								
ii. Line Tightness Test ⁵								
iii. Vapor Monitoring ⁵								
iv. Ground Water Monitoring ⁵								
m. Other state approved method (specify):								
n. Leak detection not required at this facility because: the UST system at this facility is not regulated (e.g., UST system at this facility stores heating oil for onsite use).								
 Leak detection not required at this facility because: the UST system at this facility is a wastewater treatment tank system (e.g. oil/water separator tank). 								

NOTIFICATION FOR ACTIVITIES INVOLVING UNDERGROUND STORAGE TANK SYSTEMS (USTs)

UST-8

US1-8 NOTIFICATION FOR ACT	IVITIES IN	IVOLVING	UNDERGR	COUND 31	ORAGE 17	AINK STST	EIVIS (UST:	S) ZDEU
D. Leak detection (LD) (Continued)			ı		T		ı	
	Tank No.		Tank No.		Tank No.		Tank No.	
Date leak detection method above initiated								
Monitoring console manufacturer/model								
Automatic line leak detector manufacturer /model								
Interstitial sensor manufacturer/model – tank								
Interstitial sensor manufacturer/model – piping								
Interstitial sensor manufacturer/model – spill prevention equipment								
Enter the dispenser number(s) in each column that will have the same make/model of interstitial sensor. If all dispenser interstitial sensors will be the same then enter "ALL" as the number in column 1 and complete only column 1. Dispensers with the same interstitial sensors only must be entered in one of the columns with a list of the dispensers that have that model interstitial sensor.								
	Dispenser #	(s)	Dispenser #	#(s)	Dispenser #	(s)	Dispenser #	ŧ(s)
Interstitial sensor manufacturer/model – UDC								
Interstitial monitoring leak detection is required for all UST systems installed on or after 11/1/2007. You must enter one of the following choices - Tank: Vacuum, Pressure, or Hydrostatic; Piping: Sump sensor, Vacuum, Pressure, or Hydrostatic. Interstitial monitoring leak detection is also required for all UST systems that store a hazardous substance or that are located between 100 and 500 feet of a public water supply well or between 50 and 100 feet of any other well used for human consumption or within 500 feet of a protected surface water classified as High Quality Water (HQW), Outstanding Resource Water (ORW), Water Supply I (WS-I), Water Supply II (WS-II), or Shell Fishing (SA). (The only exception is for single-walled underground petroleum tanks in the locations described above and installed after January 1, 1991 and before May 1, 2000. Owners and operators of these tanks may use enhanced leak detection as a temporary method until January 1, 2020. Enhanced leak detection consists of 0.2 gallon per hour weekly leak rate tests using an automatic tank gauge plus annual sampling of supply wells within 500 feet for constituents of petroleum.)								
² This method is only valid for USTs 550-gallo	ns or less in o	capacity or US	STs 551-1,000	gallons that h	nave a tank dia	ameter of 48 c	or 64 inches.	
³ Can only be used if groundwater is never mo	re than 20 fee	et from ground	d surface.					
 A mechanical or electronic line leak detector testing or conduct a monthly monitoring methan electronic line leak detector). This method is only valid for Field Constructed 	nod (e.g., stati	stical inventor	ry reconciliation	n, interstitial r				
E. Corrosion protection (CP) [ch	aak any math	ad or combine	tion of motho	do that apply]	[Defer to 15A		201 and 0202	<u> </u>
E. Corrosion protection (CF)	Tank No.	od of combina	Tank No.	us mar appryj	Tank No.	NCAC ZN .03	01 and .0302] Tank No.	
	Tank	Piping	Tank	Piping	Tank	Piping	Tank	Piping
Sacrificial anodes								
Impressed current								
Fiberglass Reinforced Plastic (FRP)								
Flexible Pipe]	
Steel/FRP Composite]		
Steel/Polyurethane Composite								
Internal lining								
Other (specify)	1							
None								
Date CP method above installed			_					
F. Flexible connectors, Submersible	pumps, a	nd Riser p	ipes					
	Tank No.				Tank No.		Tank No.	
	Tank	Dispenser	Tank	Dispenser	Tank	Dispenser	Tank	Dispenser
Flex connector is present ¹								
Flex connector is isolated from the ground ¹								
If "No", cathodic protection method ²								

F. Flexible connectors, Submersible	e pumps, a	and Riser p	ipes (Con	t)				
	Tank No.		Tank No.		Tank No.		Tank No.	
	Tank	Dispenser	Tank	Dispenser	Tank	Dispenser	Tank	Dispenser
Submersible pump (STP) is isolated from ground ¹ (pressurized piping only)								
If "No", cathodic protection method ²								
Riser pipes and/or other metal fittings are isolated from ground ¹								
If "No", cathodic protection method ²								
¹ Enter one of the following choices: Yes, No ² Enter one of the following choices: IC (Impressed Co	ırrent), SA (Sacr	ificial Anode), N	(None)					
G. Spill/Overfill Protection								
	Tank No.		Tank No.		Tank No.		Tank No.	
Spill Prevention Equipment Type (Enter Catchment Basin, None, or Not Required ¹)								
Spill Prevention Equipment Manufacturer								
Spill Prevention Equipment Model								
If double-walled, method of monitoring interstice ²								
Date spill prevention listed above installed								
Overfill Prevention Equipment Type (Enter Automatic shutoff, Alarm at tank, Ball float ³ , None, or Not Required ¹)								
Overfill Prevention Equipment Manufacturer								
Overfill Prevention Equipment Model								
Date overfill prevention listed above installed								
¹ Not Required is only valid for USTs that are a	always filled by	transfers that	are 25 gallor	ns or less.	•		-	
² Enter one of the following choices: Floats	sensor, Vacuu	m, Pressure, F	Hydrostatic, or	None				
³ Ball Floats cannot be used with coaxial vapor cannot be installed after June 1, 2017.	recovery or s	uction piping s	ystems. In ac	cordance with	15A NCAC 2	N .0301, new	ball float vent	valves
H. Stage I Vapor Recovery (For Ga	soline UST	s only):						
	Tank No.		Tank No.		Tank No.		Tank No.	
Combined annual throughput (gallons)								
Coaxial system			[
Dual point system			[
Vapor recovery is not required for this UST*	[[
Date installed								
* Stage I vapor recovery equipment must be in vapor recovery: a) tanks that are 550 gallons 1979; and c) tanks at facilities that have a c	s in capacity o	r less; b) tank	s that are 2,00	00 gallons in c	apacity or les			
VII. OUT OF OPERATION UST SYS	TEMS							
	Tank No.		Tank No.		Tank No.		Tank No.	
Date permanently closed (removed or fill with solid, inert material)								
Date temporary closure began								
Date temporary closure ended				<u></u>				<u></u>

NOTIFICATION FOR ACTIVITIES INVOLVING UNDERGROUND STORAGE TANK SYSTEMS (USTs)

UST-8

UST-8 NOTIFICATION FOR ACTIVITIES INVOLVING UNDERGROUND STORAGE TANK SYSTEMS (USTs)



VIII. FINANCIAL RESPONSIBILITY (for Regulated Petroleum USTs ONLY)

The financial responsibility regulations (15A NCAC 20) require that owners and operators of regulated petroleum USTs assure the availability of funds to pay for assessment and cleanup costs in the event of a leaking tank*. The payment of annual tank operating fees into the State Trust Funds fulfills a major portion of the financial responsibility requirements. However, to completely fulfill the requirements, additional funds must be assured by one or more of the mechanisms listed below. The amount of additional financial responsibility required (at a minimum) is the sum of the "3rd Party (\$100,000.00)" and "Cleanup (\$20,000.00)" State Trust Fund deductibles plus \$600/tank (scaling factor). The State Trust Funds may not be used to cover the amount of the deductibles. Federal and state governments owning regulated petroleum UST systems are exempt. Tank Owner is providing Financial Responsibility Tank Operator is providing Financial Responsibility (Check all financial responsibility mechanisms that apply): ☐ Self-insurance ☐ Escrow account ☐ Corporate guarantee ☐ Local government bond rating test ☐ Insurance and risk retention group coverage Local government financial test Policy # ■ Local government guarantee Insurer ☐ Local government dedicated fund None ☐ Surety bond Other ☐ Letter of Credit ☐ Insurance pools Period of Coverage: ☐ I am attaching proof of financial responsibility and a Certification of Financial Responsibility form. I have previously submitted proof of financial responsibility and a Certification of Financial Responsibility form to DWM and there have been NO changes made since that submittal. IX. CERTIFICATION AND ACKNOWLEDGEMENT (Read and Sign After Completing Sections I - VII) I certify, under penalty of law, that I have personally examined and am familiar with the information submitted in this and all attached documents; and that based on my inquiry of those individuals responsible for obtaining this information, I believe that the submitted information is true, accurate, and complete. In addition, I certify that all applicable State and Federal UST requirements have been complied with. If signing as an officer of a corporation, representative of a public agency, administrator of an estate, or as having power of attorney, you must provide a copy of the legal document that proves you can legally sign in such capacity. The owner must certify if providing financial responsibility. Print Name of Owner or Authorized Representative Print Title of Owner or Authorized Representative Signature Date Signed The operator must certify if providing financial responsibility. Print Name of Operator or Authorized Representative Print Title of Operator or Authorized Representative Signature Date Signed Penalties: Pursuant to N.C.G.S.143-215.94W any UST system owner or operator who knowingly fails to notify or submits false information shall be subject to a civil penalty not to exceed \$10,000 per day, per violation. PAYMENT OF ANNUAL UST OPERATING FEES If this form is being used to notify DWM of USTs which have not been previously registered, annual operating fees may be due.

Contact us at (919) 707-8171 to determine the amount of fees that are due.

A check (made payable to DEQ-UST) for the annual operating fees must be submitted with this form